LAYING INSTRUCTION SHEET – HELIXA TP[®] WALL PROTECTOR BOARD

Before gluing, unpack all the tiles onto a flat surface so that they recover their characteristics (tile decompression).

I. THE WALL

The wall must be flat, clean and dry. Clean and brush beforehand if necessary. The "WALL PROTECTOR" boards are made to be used on a plastered, wooden, steel or block wall, etc. There must be no laitance, dust, oil or grease on the surface.

II. THE GLUE

Use exclusively our HIGH TACK mastic glue – two 290ml-cartridges for 1 kit. Please read with caution instructions for use of the HIGH TACK glue.

III. LAYING



(Glue gun not provided)

Apply dots of HIGH TACK glue on both board and wall. Double gluing necessary.

If the « WALL PROTECTOR » boards have no support on the ground, use a small wooden square file nailed to the wall in order to sustain the tiles.

Put to level

Fixation with steel nails if you have a concrete, block or wooden wall.



Press firmly the "WALL PROTECTOR" board against the wall and hit slowly the surface with a rubber mallet. Lay 2 red boards then one black board. Repeat as many times as necessary.

You need to check regularly the evenness of the «WALL PROTECTOR » boards

WARNING: Leave no space between the boards. WAIT 48H BEFORE REMOVING THE STEEL NAILS

Models, drawings and names are registered. No copy or reprography is permitted without prior written authorization. This manual was reviewed in February 2016 and may be updated; please make sure this is the latest version. FRANCE CONSTRUCTION Sols Sportifs et Techniques ZAC des Bousquets – 165 rue de l'Initiative – F-83390 CUERS

ZAC des Bousquets – 165 rue de l'Initiative – F-83390 CUERS TEL.: +33 (0)4 94 14 91 91 – FAX.: +33 (0)4 94 14 93 93 WEBSITE: www.hexdalle.com - E-MAIL: contact@hexdalle.com Page 1 out of 2



Respect drying time. Remove the steel nails after 24h.

IV. CUTTINGS

The boards can be cut very easily thanks to a retractable utility knife or a sabre jigsaw

V. LAYING TOOLS

- Level, •
- Measuring tape, chalk,
- Glue gun,
- Chalk line, •
- Rubber mallet,
- Wooden square file and steel nails if necessary, •
- retractable utility knife, electric sabre jigsaw, •
- Straight ruler, •
- Concrete steel nails. •