

PRODUCT DATA SHEET –FC 41 SOLVENT

I. CHEMICAL BASE / APPLICATIONS

Mix of urethane-grade solvents designed for cleaning tools soiled with PU 93 or PU 59 glue as well as for smoothing synthetic agglomerates produced from rubber granules and polyurethane bonding agents. May be used for smoothing coloured quartz agglomerates bound with an epoxy bonding agent.

II. PRODUCT PROPERTIES

Appearance Clear liquid
DIN 52 002

Density g/cm³-25°C 1.05 g/cm³
DIN 53 217

Viscosity (mm²/s) – 25°C 2.47
DIN 53018/1+2

Flash point in °C 95°C
(Open Cup - COC)

Vapour pressure <2.5 mbar
Mm Hg at 20°C

Miscibility: Good miscibility with polyols, solvents, polyisocyanate-based prepolymers and some plasticizers.

III. PRECAUTIONS

Read the safety sheet before use. As this product has degreasing properties, avoid contact with the skin. Good general ventilation should be sufficient for most cases.

Protect hands by wearing gloves impervious to the product in the event of extended contact.

Protect eyes by wearing safety glasses.

Protect the body by storing work clothes separately. Wash hands at each break and when the work is finished.

This is a propylenic glycol ether-based product.

As this product is not classified as dangerous, there is no professional exposure limit.

IV. PACKAGING

5 Kg or 1Kg.

V. STORAGE

Keep the container tightly closed, away from sunlight and moisture.

VI. NOTE

Our advice on technical applications is given without any guarantee whatsoever.

Buyers of our products are responsible for their application or their transformation, even as regards any third party rights.

Manufactured by Stockmeier Urethanes France SAS

Models, drawings and names are registered. No copy or reprography is permitted without prior written authorization.
This manual was reviewed in February 2016 and may be updated; please make sure this is the latest version.

FRANCE CONSTRUCTION Sols Sportifs et Techniques
ZAC des Bousquets – 165 rue de l'Initiative – F-83390 CUERS
TEL.: +33 (0)4 94 14 91 91 – FAX.: +33 (0)4 94 14 93 93
WEBSITE: www.hexdalle.com - E-MAIL: contact@hexdalle.com